



Lafarge Magnolia® Buff, Dark & Ultra Dark Masonry Cement

LAFARGE

Lafarge masonry cements are pure and natural. No added pigment. No fading. No deterioration. Derived only from the basic ingredients used in our manufacturing process, the shades are uniform, stable and very easy to clean. All three color masonry cements offer the excellent working characteristics of our Magnolia Mason's Mix – from superior board life and yield, to great workability and durability. These rich natural colors are designed to enhance commercial and residential structures, and each product meets all applicable ASTM specifications.





LAFARGE MAGNOLIA BUFF, DARK & ULTRA DARK MASONRY CEMENT

Precautions

Direct contact with wet cement should be avoided. If contact occurs, the skin should be washed with water as soon as possible. Exposure can cause serious, potentially irreversible tissue destruction in the form of chemical (caustic) burns. If cement gets into the eyes, immediately rinse thoroughly with water and seek medical attention. For more information, reference the applicable Lafarge Material Safety Data Sheet (MSDS). The MSDS should be consulted prior to use of this product and is available upon request and online at www.lafarge-na.com.

Limited Warranty

Lafarge warrants that Lafarge Magnolia Buff, Dark and Ultra Dark Masonry Cement meets the requirements of ASTM C 91. Lafarge makes no other warranty, whether of merchantability or fitness for a particular purpose, with respect to Magnolia Buff, Dark and Ultra Dark Masonry Cement. Having no control over its use, Lafarge will not guarantee finished work in which Magnolia Buff, Dark and Ultra Dark Masonry Cement is used.

Product Name

Lafarge Magnolia Buff
Lafarge Magnolia Dark Mason's Cement
Lafarge Magnolia Ultra Dark

Manufacturer

Lafarge Building Materials Inc.
12950 Worldgate Drive
Suite 500
Herndon, Virginia 20170
www.lafarge-na.com

Product Description

Basic Use:

These masonry cements are specially formulated and manufactured to produce, buff, dark grey and ultra dark grey colors without the further addition of color pigments. They are specially designed for use with brick.

Types:

Produced in Type N strength level for use in preparation of ASTM specification C 270, Type N, without further addition of Portland cement or hydrated lime.

Technical Data

Applicable Standard: These masonry cements conform to ASTM C 91, *The Standard Specification for Masonry Cement*. Each product produces a Type N mortar as outlined in either the property or proportion specification requirement of ASTM C 270, when properly mixed with mason's sand and clean, potable water.

Limitations

Colors of these masonry cements are by design produced without the use of pigments. They should be mixed with sand and clean water to produce a masonry mortar without the further addition of Portland cement or hydrated lime and are not recommended for stucco.

Contact your Lafarge Office for specific product information, availability and ordering.

Lakes and Seaway Business Unit

Bingham Farms, Michigan
Phone: 248-594-1991

River Business Unit

Lee's Summit, Missouri
Phone: 816-251-2100

U.S. East Business Unit

Alpharetta, Georgia
Phone: 678-746-2000

